



RIPPLE LAND – KALAPPURA ALAPPUZHA

Ph 0477-2244460,9400008692

e-mail: rippleland@ktdc.com

GSTIN: 32AABCK0385J1ZP

KTDC/ RL/ Est/ 81/ 2025

22/08/2025

QUOTATION

Sub:-“Quotation for the construction of compound wall at KTDC Ripple Land – Alappuzha”;- Reg

Competitive quotations are invited for the construction of 21 meter Compound wall at KTDC Ripple Land Alappuzha as per the details attached.

The quotation details % form can be have from the office of KTDC Ripple Land during the office hours from 22/08/2025 to 28/08/2025.

The quotation shall reach the office of the Manager KTDC Ripple Land on or before 1.00 PM 29-08-2025. The quotations will be opened at 2.00 PM on the same day in the presence of available tenderers.

If the last date mentioned falls as a holiday or Hartal, the very next working day will be treated as the last date.

The Manager KTDC Ripple Land reserves the right to reject any or all the tenders received without assigning any reason.

Manager

Reconstruction of compound wall at Ripple Land Alappuzha-General Civil Work					
Sl. NO.	Specification	Quantity	Unit	Basic rate	Total Amount in Rs
	compound wall				
1.001	2.8.1 Earth work in excavation by mechanical means (Hydraulic excavator) /manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan),including dressing of sides and ramming of bottoms, lift up to 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed,within a lead of 50 m.All kinds of soil	7.56	cum		
1.002	4.1.8 Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level:1:4:8 (1 Cement : 4coarse sand (zone-III) derived from natural sources : 8 graded stone aggregate 40 mm nominal size derived from natural sources)	1.26	cum		
1.003	7.1.1 Random rubble masonry with hard stone in foundation and plinth including levelling up with cement concrete 1:6:12 (1 cement : 6 coarse sand : 12 graded stone aggregate 20 mm nominal size) up to plinth level with:Cement mortar 1:6 (1 cement : 6 coarse sand)	7.56	cum		
1.004	5.22.6 Steel reinforcement for R.C.C work including straightening, cutting, bending, placing in position and binding all complete upto plinth levelThermo - Mechanically Treated bars of grade Fe-500D or more	90.534	kilogram		
1.005	5.9.1 Centering and shuttering including strutting, etc. and removal of form for:Foundations, footings, bases of columns, etc for mass concrete	4.29	sqm		
1.006	5.1.2 Providing and laying in position specified grade of reinforced cement concrete,excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level:1:1:5:3 (1 cement 1.5 coarse sand :3 graded stone aggregate 20 mm nominal size derived from natural sources)	0.945	cum		
1.007	50.6.1.7 Solid block masonry using pre cast solid blocks (Factory made) of size 40x20x15cm or nearest available size confirming to IS 2185 part I of 1979 for foundation and plinth with thickness 15 cm in : CM 1:6 (1 cement : 6 coarse sand) etc complete	6.66	cum		
1.008	13.1.1 12 mm cement plaster of mix:1:4 (1 cement : 4 fine sand)	101.5	sqm		
	Grand total Amount in Rs inclusive of GST				